

STANDART YASSI HOPARLÖR KABLOLARI STANDARD FLAT SPEAKER CABLES



KULLANIM ALANLARI

0.50mm² ile 4.00mm² iletken alanları arasında üretimi yapılan bu kablolar esnek ve çok telli damar yapılarıyla ses bandında yüksek performans göstermektedir.

ELEKTİRİKSEL ÖZELLİKLER

Çalışma Gerilimi	300 V.
Test Gerilimi	2000 V.
Yalıtım Direnci	>100 MOhm x km
İletken Direnci	0.50mm ² / < 39 Ohm / km 0.75mm ² / < 26 Ohm / km 1.50mm ² / < 13.5 Ohm / km 2.50mm ² / < 8 Ohm / km 4.00mm ² / < 5 Ohm / km

MEKANİK ÖZELLİKLER

Min. Bükme Yarıçapı	Sabit Tesis Hareketli Tesis	5 x Kalınlık 10 x Kalınlık
Çalışma Sıcaklığı	Sabit Hareketli	-25°C +70°C - 5°C..... 70°C

APPLICATION

The conductor size of this type cable changes between 0.5mm² and 4.00 mm² . They show high performance in audio band.

ELECTRICAL CHARACTERISTICS

Rating Voltage	300 V.
Test Voltage	2000 V.
Insulation Resistance	>100 MOhm x km
Conductor Resistance	0.50mm ² / < 39 Ohm / km 0.75mm ² / < 26 Ohm / km 1.50mm ² / < 13.5 Ohm / km 2.50mm ² / < 8 Ohm / km 4.00mm ² / < 5 Ohm / km

MECHANICAL CHARACTERISTICS

Min. Bending Radius	Fixed Installation Mobile Use	5 x Thickness 10 x Thickness
Temperature Range	Static Flexing	-25°C +70°C - 5°C..... 70°C

SEMBOL SYMBOL	ÜRÜN KODU CODE NO.	KESİT CROSS SECTION	DIŞ ÖLÇÜ OVERALL MEASURE	STANDART AMBALAJ STANDARD LENGTH
EK.H2016	20120016	2x0.50mm ²	2.1x4.5mm	100 m.
EK.H2024	20120024	2x0.75mm ²	2.3x4.9mm	100 m.
EK.H2530	20125030	2x1.50mm ²	2.6x5.5mm	100 m.
EK.H2550	20125050	2x2.50mm ²	3.3x7.0mm	100 m.
EK.H3056	20130056	2x4.00mm ²	4.3x8.8mm	100 m.